

Panasonic® Nickel Cadmium Batteries Solder Tabbed Version (Cont.)

Size	(V)	Capacity C/5 (mAh)	Dimensions Inch (mm) Dia. x Height	Weight* Oz. (gram)	Std. Chg @ 16hrs (mA)	Quick Charge (mA) (hrs.)	Digi-Key Part No.	Pricing			
								1	10	Pkg.	Carton
<i>Standard Type (Solder Tabbed)</i>											
N	1.2	180	0.47 x 1.18 (12.0 x 30.0)	0.28 (8.0)	18	45 6.0	P112T-ND	2.56	23.04	358.40/200	1416.96/1200
AAA	1.2	250	0.41 x 1.75 (10.5 x 44.5)	0.35 (10)	25	75 5.0	P254T-ND	2.79	25.09	446.00/200	2286.27/1800
2/3C	1.2	1000	1.02 x 1.22 (25.8 x 31.0)	1.59 (45)	100	333 4.5	P238T-ND	6.96	62.66	278.50/50	1253.25/300
C	1.2	2200	1.00 x 1.94 (25.3 x 49.3)	2.65 (75)	220	730 4.5	P163T-ND	6.64	59.78	106.28/20	956.52/240
C	1.2	2400	1.02 x 1.97 (25.8 x 50.0)	2.65 (75)	240	1500 2.4	P108T-ND	7.77	69.91	124.28/20	1118.52/240
D	1.2	4000	1.30 x 2.40 (33.0 x 61.0)	4.90 (139)	400	— —	P124T-ND	11.08	88.66	88.66/10	664.95/100
<i>High Temperature "H" Type (Solder Tabbed)</i>											
1/3AA	1.2	110	0.57 x 0.69 (14.5 x 17.5)	0.23 (6.5)	11	— —	P109T-ND	2.26	20.34	216.96/120	2757.89/2400
AA	1.2	500	0.57 x 1.97 (14.5 x 50.0)	0.74 (21)	50	— —	P161T-ND	2.58	23.22	82.56/40	1238.40/800
SC	1.2	1200	0.91 x 1.69 (23.0 x 43.0)	1.69 (48)	120	— —	P091T-ND	4.06	36.56	325.00/100	975.00/400
C	1.2	1800	1.02 x 1.97 (25.8 x 50.0)	2.55 (73)	180	— —	P122T-ND	7.14	64.28	114.28/20	1028.52/240
C	1.2	2300	1.02 x 1.97 (25.8 x 50.0)	2.75 (78)	230	— —	P090T-ND	7.77	69.91	124.28/20	1118.52/240
D	1.2	4000	1.30 x 2.40 (33.0 x 61.0)	4.90 (139)	400	— —	P258T-ND	11.08	88.66	88.66/10	664.95/100
<i>High Capacity "E" Type (Solder Tabbed)</i>											
SC	1.2	1500	0.91 x 1.69 (23.0 x 43.0)	1.69 (48)	150	500 4.5	P156T-ND	4.49	40.39	430.80/120	1292.40/480
D	1.2	4400	1.30 x 2.40 (33.0 x 61.0)	4.93 (140)	440	— —	P158T-ND	11.21	89.66	89.66/10	672.45/100
<i>High Rate Discharge and Rapid Charge "P" Type (Solder Tabbed)</i>											
SC	1.2	1200	0.91 x 1.69 (23.0 x 43.0)	1.66 (47)	120	1200 1.5	P240T-ND	3.94	35.44	315.00/100	945.00/400
<i>Rapid Charge "R" Type (Solder Tabbed)</i>											
2/3AA	1.2	300	0.57 x 1.11 (14.5 x 28.2)	0.42 (12)	30	300 1.5	P234T-ND	2.49	22.41	398.40/200	2542.96/2000
AA	1.2	600	0.57 x 1.90 (14.5 x 48.3)	0.74 (21)	60	600 1.5	P229T-ND	2.55	22.91	81.44/40	1221.60/800
AA	1.2	700	0.57 x 1.90 (14.5 x 48.3)	0.78 (22)	70	700 1.5	P253T-ND	2.21	19.85	70.56/40	1058.40/800
4/5SC	1.2	1200	0.91 x 1.30 (23.0 x 33.0)	1.38 (38)	120	1000 1.6	P232T-ND	3.94	35.44	315.00/100	1417.50/600
SC	1.2	1300	0.91 x 1.69 (23.0 x 43.0)	1.66 (47)	130	1300 1.5	P159T-ND	2.86	25.76	274.80/120	824.40/480
SC	1.2	1400	0.91 x 1.69 (23.0 x 43.0)	1.69 (48)	140	1400 1.5	P233T-ND	3.36	30.26	269.00/100	968.40/480
SC	1.2	1800	0.91 x 1.69 (23.0 x 43.0)	1.73 (49)	180	1800 1.5	P089T-ND	4.99	44.89	399.00/100	1197.00/400
C	1.2	2800	1.02 x 1.97 (26.0 x 50.0)	2.79 (79)	280	2800 1.5	P190T-ND	8.14	73.28	130.28/20	1172.52/240
D	1.2	5000	1.30 x 2.40 (33.0 x 61.0)	5.10 (145)	500	5000 1.5	P257T-ND	13.23	—	105.86/10	793.95/100
<i>Super High Capacity and Rapid Charge "S" Type (Solder Tabbed)</i>											
AA	1.2	800	0.57 x 1.90 (14.5 x 48.3)	0.71 (20)	80	800 1.5	P097T-ND	2.51	22.55	80.16/40	1202.40/800
AA	1.2	1000	0.57 x 1.97 (14.5 x 50.0)	0.81 (23)	100	1000 1.5	P092T-ND	3.46	31.10	110.56/40	1658.40/800
5/4AA	1.2	1200	0.57 x 2.56 (14.5 x 65.0)	1.09 (31)	120	1200 1.5	P093T-ND	4.72	42.44	188.60/50	1697.40/600
2/3A	1.2	600	0.67 x 1.12 (17.0 x 28.5)	0.63 (18)	60	600 1.5	P235T-ND	3.08	27.72	123.20/50	1330.56/720
4/5A	1.2	1500	0.67 x 1.69 (17.0 x 43.0)	0.95 (27)	140	1400 1.5	P255T-ND	4.46	40.14	642.24/180	1926.72/720
A	1.2	1400	0.67 x 1.97 (17.0 x 50.0)	1.16 (32)	140	1400 1.5	P095T-ND	3.97	35.71	571.32/180	1713.96/720
A	1.2	1600	0.67 x 1.97 (17.0 x 50.0)	1.16 (33)	160	1600 1.5	P256T-ND	4.52	40.66	650.52/180	1951.56/720
5/4SC	1.2	2300	0.91 x 1.97 (23.0 x 50.0)	2.24 (57)	230	2000 1.6	P096T-ND	8.23	74.07	790.08/120	1777.68/360

* See "How To Order" for note on shipping charges on prepaid orders.

Battery Packs with Panasonic® Batteries

For Memory Backup, Power Tools, Radio Controlled and Other Endless Applications

All battery packs are made using our high quality Panasonic cells. Shown are standard configurations. If you have a special need or a configuration that you do not see, give us a call for further information. Packs are available in nearly all sizes of Nickel-Cadmium, NiMH, Lithium, and Alkaline cylinder batteries.

Digi-Key is not approved by any state or federal agency as an authorized supplier of product for medical, life support or life sustaining devices or systems.

Style	Volts	Cells	Configurations	Diagram
F021	2.4	2		
F031	3.6	3		
F041	4.8	4		
F051	6.0	5		
F061	7.2	6		
F071	8.4	7		
F081	9.6	8		
F091	10.8	9		
F101	12.0	10		
F022	4.8	4		
F023	7.2	6		
F024	9.6	8		
F025	12.0	10		

Style	Volts	Cells	Configurations	Diagram
L021*	2.4	2		
L031*	3.6	3		
L041*	4.8	4		
L051*	6.0	5		
L022	4.8	4		
L032	7.2	6		
L042	9.6	8		
L052	12.0	10		
L023	7.2	6		
L024	9.6	8		
L025	12.0	10		

* Styles L021, L031, L041 and L051 are not available in nickel-metal hydride batteries.

HOW TO ORDER: P - - ND

Call for pricing on any standard or custom battery pack

Select Digi-Key Part No. of any Cylinder Type Battery

Select Style of Battery Pack From Chart